

Technical Data Sheet

Page 1 of 1

Properties:	AKEMI® Ceramics Mildew Remover is a fast-acting, slightly alkaline cleaning agent based on active chlorine compounds. The product is free of solvents.		
Application Area:	AKEMI® Ceramics Mildew Remover rapidly and thoroughly removes mildew and mould stains in sanitary areas on cement- and silicone joints, tiles and plastic parts as well as on natural stones, masonry, plaster or other mineral surfaces.		
Instructions for Use:	<ol style="list-style-type: none">1. Evenly spray from a distance from approx. 25 cm.2. Do not let dry. Repeat if necessary.3. Allow to work for 10-20 minutes, thoroughly clean with water and a brush made of synthetic material.4. Repeat cleaning in case of stubborn dirt.		
Special Notes:	<ul style="list-style-type: none">- The product is registered by Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (BAuA) under the no. N-38700 and by Bundesinstitut für Risikobewertung (BfR) under the no. 2036171.- Wear suitable protective gloves.- Do not allow contact with plants, otherwise wash with plenty of water.- Do not allow contact with metal, wood, clothing or similar to avoid discolouring or bleaching. If in doubt try at an inconspicuous area.- Do not refill used material in the original container.- Protect against direct sunlight and heat.- The spray cap of the spray bottle should be removed after use, cleaned with water and replaced by the original closure.- For adequate waste disposal container must be completely emptied.		
Technical Data:	Coverage:	approx. 10 – 20 m ² /liter	
	Colour:	yellowish transparent	
	Density:	approx. 1.10 g/cm ³	
	pH value:	approx. 11	
Storage:	1 year approx. if stored in cool place free from frost in its tightly closed original container.		
Health & Safety:	Read Material Safety Data Sheet before handling or using this product.		
Important Notice:	The above information is based on the latest stage of development and application technology. Due to a multiplicity of different influencing factors, this information – as well as other oral or written technical advises – must be considered as non-binding hints. The user is obliged in each particular case to conduct performance tests, including but not limited to trials of the product, in an inconspicuous area or fabrication of a sample piece.		

TDS 02.10