

Page 1 of 1

Technical Data Sheet

Properties:	AKEMI [®] Defoamer is a low viscous defoaming concentrate based on silicone oils emulsified in water and additional auxiliary materials. The product is characterized by the following properties:	
	 highly effective, therefore very economically neutral pH-value almost odourless easy application by use in wastewater tanks 	
Application Area:	AKEMI [®] Defoamer is used as an additive in wastewater tanks of almost all types of cleaning machines (e.g. cleaning automats, vacuum sweepers etc.). It reduces the formation of foam very effectively; in this way mechanical cleaning flows smoothingly.	
Instructions for Use:	 Shake briefly before use. Add 20 - 200 ml of defoaming concentrate to a wastewater tank with a capacity of 10 litres. This quantity corresponds to a dosing percentage of 0.2 - 2 %. When using bigger tanks, dilute the corresponding quantity of product with 1 - 2 litres of water. If necessary, additional concentrate can be added. 	
Special Notes:	 For industrial use only. Do not bring the defoaming concentrate in contact with surfaces to be treated. Do not add to cleaning agents. For adequate waste disposal container must be completely emptied. 	
Technical Data:	Colour: Density: pH value (concentrate):	milky approx. 1.0 g/cm³ approx. 7
Storage:	2 years if stored in cool place free from frost in its tightly closed original container.	
Health & Safety:	Read Material Safety Data Sheet before handling or using this product.	
Important Notice:	The above information is based on the latest stage of development and application technology. Due to a multiplicity of different influencing factors, this information – as well as other oral or written technical advises – must be considered as non-binding hints. The user is obliged in each particular case to conduct performance tests, including but not limited to trails of the product, in an inconspicuous area or fabrication of a sample piece.	